



Double BALL BEARINGS CO, LTD



6207LLUNR Bearing 2D drawings and 3D CAD models

35,000 mm x 72,000 mm x 17,000 mm NTN
6207LLUNR deep groove ball bearings

Bearing No. 6207LLUNR

Size	35x72x17 mm
Bore Diameter	35,000 mm
Outer Diameter	72,000 mm
Width	17,000 mm
d	35,000 mm
D	72,000 mm
B	17,000 mm
C	17,000 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359565478
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	Yes
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric



Double BALL BEARINGS CO, LTD

Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal With Snap Ring -20 To 120 Deg C Shell Alvania Prelubricated
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Weight / LBS	0.635
Bore	1.378 Inch 35 Millimeter
Outside Diameter	2.835 Inch 72 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.669 Inch 17 Millimeter
bore diameter:	35 mm
static load capacity:	15300 N
outside diameter:	72 mm
precision rating:	ISO Class 0
overall width:	17 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel



Double BALL BEARINGS CO, LTD

row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	17 mm
snap ring included:	With Snap Ring
outer ring width:	17 mm
internal clearance:	CN
maximum rpm (grease):	6300 rpm
operating temperature range:	-40 to 120 ° C
fillet radius:	1 mm
dynamic load capacity:	25700 N
manufacturer product page:	Click here